

MiniMax™

Better start up

- A lower pan: The height of the MiniMax is reduced to 60 mm. This way the day-old-chicks can see the feed easily and have an excellent access to the feed.
- 360° flooding keeps the MiniMax-pan full of feed.

Highly efficient broiler production

- The stepped bottom pan optimizes the feed intake.
- The anti-waste rim eliminates practically all feed waste.

Control pan with LED light option

- A LED light kit is available as an option for the control unit. The LED light in the control pan attracts the birds and guarantees a completely filled feeding line and feeding pans.

Cleaning option

- When selecting the cleaning option, even the inner side of the cone can be cleaned in an easy way.



Animal info			
	Light (<1,8 kg)	Medium (1,8-3 kg)	Heavy (>3 kg)
Number of birds/pan (*)	84-100	50-84	40-50
Density birds/m ² (**)	21-24	13-21	10-13
Max. daily feed intake (g/bird)	170	190	220
General & Technical info			
Grill	Struts	14	
	Opening between struts	71 mm	
Pan	Material	Polypropylene (support in nylon)	
	Rim height (including grill)	60 mm	
	Diameter	330 mm	
Transport: Drive unit (***)		350 rpm	
Transport capacity (***)		450 kg/h	
Outside diameter of tubes		44,5 mm	
Max. length per fill point		150 m	
Suspension		max. every 3 m	
Average height		3,25 m	
(*) based on 6,6mm/kg and circumference of Minimax is 998 mm (**) based on 39kg/m ² (***) based on 50 Hz			